



The FlexiTank reservoir revolutionises water storage, it is everything you need in one compact box. It requires no tools for assembly, reduces storage and shipping costs and takes just minutes to assemble. It really couldn't be simpler.

Contents

1x 1/2" click fit male connector

9x Support Poles (200 gallon) **11x Support Poles** (265 gallon)

1x FlexiTank

1x ½" Tap

1

2

3

1x Support Band



46 x 5 x 7"/ 13.7lb When full of water: 35.5" Diameter x 46" High

35 x 8 x 6.5"/16.5lb When full of water: 47" Diameter x 35.5" High

Assembly Instructions

Unpack the contents - ensure all parts are correct.

Unfold and open your blue FlexiTank reservoir.

Attach the tap to the bottom of the FlexiTank by pushing it through the hole. Keep the tap at a 90 degree angle anticlockwise and ensure there is a rubber washer on the outside and the inside of the reservoir. Tighten the nut as far as possble by hand. Insert all support poles into the side sleeves of the FlexiTank

The Flexitank reservoir is now ready to be turned upright and moved into place. Ensure that the Flexitank reservoir is placed on a flat and smooth surface to prevent damage to the plastic.

Place the support band around the FlexiTank BEFORE it is filled with water. Slide band down the tank so it is positioned just above the tap. As the tank is filling ensure that the band is level around the tank.

Fill the Flexitank reservoir. Once full with water, twist the tap 90 degrees clockwise to the correct position.

Do not attempt to move the FlexiTank when it has ANY amount of water in it. The FlexiTank must be completely drained before moving. Failure to do so will void your warranty. DO NOT MOVE THE TANK WHEN IT IS FULL.

The FlexiTank reservoir comes with a 6 month guarantee, covering manufacturing defects. Any misuse of the product is not covered by the guarantee.

www.autopot-usa.com info@autopot-usa.com (+1) 702 338-0373

