

PERFORMANCE

°F %RH	80 60	75 50
Water Removal (P/Day)	176	116
Efficiency (P/kWh)	7.7	4.5
Energy Factor (L/kWh)	3.6	2.1

ELECTRICAL

°F %RH	80 60
Supply Voltage	110-120
Current Draw	10.0A
Power	1,200W
Power Cord	14 ga NEMA 5-15p
CFM	380
BTU (Total)	12,000
BTU (Heat of Condensation)	8,000
BTU (Motor Load)	4,000

SPECS

Control Type	Onboard
Refrigerant Type	R410a
Refrigerant Amount	2 lb 12 oz
Weight	135 lb
Air Filter MERV Rating	MERV-11
Dimensions	20" x 16" x 2"
Drain Port Connection	3/4" Threaded NPT
Operating Temperature	56 F Min - 110 F Max



FEATURES

- + Added dehumidification where you need it with 12-inch recessed wheels, allowing for superior mobility
- + Portable design with 25-foot power cord
- + Onboard control, with low voltage terminal block for optional external control
- + 30-foot drain hose with internal pump capable of lifting condensate 17 feet
- + Durable stainless steel housing
- + Auto-restart in the event of power outage

Specifications are subject to change without notice. Drawings are not to scale. *See manual for details on MCA/MOP.